## Hangzhou Jiekai Chemicals Co., Ltd.

NO.227, SHIXIN BEILU RD, HANGZHOU, CHINA. Tel: 86-571-83710202 Web: www.jkpigment.com

#### Material Safety Data Sheet

## According to 91/155/EEC and ISO 11014-1

Page:1/3			
1. Identification of substance and of the company			
Trade Name: PIGMENT RED 48:4			
Hangzhou Jiekai Chemicals Co., Ltd.			
NO.227, SHIXIN BEILU RD, XIAOSHAN DISTRICT, HANGZHOU, CHINA.			
Tel: 86-571-83710202 Fax: 86-571-82163005			
2. <u>Composition/Data on components</u>			
Substance: PIGMENT RED 48:4			
CAS No: 5280-66-0 EEC Symbol: None R-Phrases: None			
3. <u>Hazards identification</u>			
No hazardous effects known			
The product is not a substance subject to mandatory marking in accordance with the EEC			
Directive 67/584/EEC Or amendments			
4. <u>First Aid measures</u>			
After inhalation: Supply fresh air.			
After eye contact: Flush with plenty of pressure water for 15 minutes, occasionally raising			
eye lids.			
After skin contact: Wash skin with mild soap and water.			
5. <u>Fire fighting measures</u>			
Suitable extinguishing media: no restriction			
Special hazards caused by the material, its combustion products or resultant gases: none			
Special personal protection equipment: none			
6. <u>Accidental release</u>			
Environmental protection conduct: Do not sweep or wash into public stretches of water,			
sewers or sites of unknown discharge paths.			
After spillage/leakage/gas/ leakage: Clean up immediately with wetting or absorbent			
material avoiding dusting.			
7. <u>Handling and storage</u>			
Handling:			
Usual precautions for nuisance dust should be observed.			
Protection against fire and explosion:			
The product is non-flammable			
Storage:			
Store in roofed places at room temperature Keep containers tightly sealed.			
Flammability Class: nor applicable.			

## Material Safety Data Sheet

## According to 91/155/EEC and ISO 11014-1

	-		Page:2/.	
Trade name: PIGMENT	RED 48:4			
8. <u>Exposure controls</u>	/personal protection	<u>n</u>		
Additional notes for	design of plants equip	ment:		
No farther details, see	sec7			
Components with wo	orkplace-related limits	to be monitored:		
Designation	%	Type of data	Unit	
Nuisance dust	100	MAK	6 mg/m3	
		TLV/TWA(USA)	10 mg/m3	
Personal protection	equipment:			
Respiratory protection	on:			
An appropriate dust fi	xer has to be used if a b	reathable dust liberated.		
9. <u>Physical and chen</u>	nical properties			
Appearance: Red pow	der	Odor: mild		
Melting point:360°C		Relative density:1.52-2.0		
Decomposition: None		Flammability: see 7handling		
Molecular formula:C1	8H15CIN2O6S	Molecular Weight: 422.84		
Tinting strength: 95-105% of the standar		Volatile matter at 105°C: 2.5% max		
Soluble matter in water: 1.5% max		Oil absorption:45-55%		
Fastness to light:8		Fastness to heat ( $^{\circ}$ C):200		
Bleeding resistance water: 5		Bleeding resistance linseed oil: 5		
Bleeding resistance ad		Bleeding resistance alkalis:4		
Bleeding resistance alcohol:3		Bleeding resistance xylone:3-4		
Bleeding resistance et				
10. Stability and rea	<u>ctivity</u>			
Hazardous decompo				
No decomposition at	proper storage and app	lication conditions		
11. <u>Toxicological Inf</u>	ormation			
Because of experience	e with product mention	ed, there are no recognizable	e hazards for huma	
beings, if it is correc	-			
12. <u>Ecological inform</u>				
Avoid filtration into	waster draining or soil.			
13. <u>Disposal conside</u>	rations			
Uses should acquain	themselves with local	regulations.		
		an approved tip or by incine eed to be sorubbed (see section	-	

#### **Material Safety Data Sheet**

According to 91/155/EEC and ISO 11014-1

Page:3/3

# Trade name: PIGMENT RED 48:4 14. <u>Transport information</u> No declaration for transport required 15. <u>Regulatory information</u> Classified according to the Directives 67/548/EEC, and their varions amendments, and labeled as below: Warning symbols: None Warning words: None Risk Phrases: None Safety Phrases: None 16. Other information Listed in EINECS and TSCA inventories.0 Intended uses: Paints. References: -(1)Occupational Exposure Limits, EH/40(HSE) -(2)Deutsche Forschungs gerneinschaft MAK-& BAT-Values. -(3)A.C.D.Cowley, Polymers Paint Journal, August 7/21, 1985.