Hangzhou Jiekai Chemicals Co., Ltd.

NO.227, SHIXIN BEILU RD, HANGZHOU, CHINA. Tel: 86-571-83710202 Web: www.jkpigment.com

Material Safety Data Sheet

According to 91/155/EEC and ISO 11014-1

Page:1/3 1. Identification of substance and of the company Trade Name: PIGMENT BLUE 15:0 Hangzhou Jiekai Chemicals Co., Ltd. NO.227, SHIXIN BEILU RD, XIAOSHAN DISTRICT, HANGZHOU, CHINA. Tel: 86-571-83710202 Fax: 86-571-82163005 2. Composition/Data on components Substance: PIGMENT BLUE 15:0 CAS No: 147-14-8 EEC Symbol: None **R-Phrases:** None 3. Hazards identification No hazardous effects known The product is not a substance subject to mandatory marking in accordance with the EEC Directive 67/584/EEC Or amendments 4. First Aid measures After inhalation: Supply fresh air. After eye contact: Flush with plenty of pressure water for 15 minutes, occasionally raising eye lids. After skin contact: Wash skin with mild soap and water. 5. Fire fighting measures Suitable extinguishing media: no restriction Special hazards caused by the material, its combustion products or resultant gases: none Special personal protection equipment: none 6. Accidental release Environmental protection conduct: Do not sweep or wash into public stretches of water, sewers or sites of unknown discharge paths. After spillage/leakage/gas/ leakage: Clean up immediately with wetting or absorbent material avoiding dusting. 7. Handling and storage Handling: Usual precautions for nuisance dust should be observed. Protection against fire and explosion: The product is non-flammable Storage: Store in roofed places at room temperature Keep containers tightly sealed. Flammability Class: nor applicable.

Material Safety Data Sheet

According to 91/155/EEC and ISO 11014-1

	10 71/155/LEC and 150 11014-1	Page:2/3	
Trade name: PIGMENT BLUE			
8. <u>Exposure controls/persona</u>			
Additional notes for design of	olants equipment:		
No farther details, see sec7			
Components with workplace-r			
Designation %	Type of data	Unit	
Nuisance dust 100	MAK	6 mg/m3	
	TLV/TWA(USA)	10 mg/m3	
Personal protection equipment	:		
Respiratory protection:			
	be used if a breathable dust liberated.		
9. <u>Physical and chemical pro</u>	<u>perties</u>		
Appearance: blue powder	Odor: mild		
Melting point: 300	Relative density:1.5-1.80	Relative density:1.5-1.80	
Decomposition: None	Flammability: see 7 han	Flammability: see 7 handling	
Molecular formula: C32H16CuN	18 Molecular Weight: 576.0	Molecular Weight: 576.07	
Tinting strength: 95-105% of the	standard Volatile matter at 105° C:	Volatile matter at 105°C: 2.5% max	
Soluble matter in water: 1.5% m	AX Oil absorption:28-62%	Oil absorption:28-62%	
Fastness to light:7-8	Fastness to heat(°C):200	Fastness to heat ($^{\circ}C$):200	
Bleeding resistance water: 5	Bleeding resistance lins	Bleeding resistance linseed oil: 5	
Bleeding resistance acid: 5	Bleeding resistance alka	Bleeding resistance alkalis:5	
Bleeding resistance alcohol:5	Bleeding resistance xyle	one:4	
Bleeding resistance ethyl acetate	: 4		
10. <u>Stability and reactivity</u>			
Hazardous decomposition prod	icts		
No decomposition at proper sto	rage and application conditions		
11. <u>Toxicological Informatior</u>	<u> </u>		
Because of experience with pro	duct mentioned, there are no recognizable	e hazards for huma	
beings, if it is correctly used an	-		
12. <u>Ecological informatio</u>	**		
Avoid filtration into waster drai	ning or soil.		
13. <u>Disposal considerations</u>			
Uses should acquaint themselve			
	by burying at an approved tip or by incine	-	
waste material processor; stack	gases may need to be sorubbed (see section	on 5 above)	

Material Safety Data Sheet

According to 91/155/EEC and ISO 11014-1

Page:3/3

Trade name: PIGMENT BLUE 15:0

14. <u>Transport information</u>

No declaration for transport required

15. <u>Regulatory information</u>

Classified according to the Directives 67/548/EEC, and their varions amendments, and labeled as below:

Warning symbols: None

Warning words: None

Risk Phrases: None

Safety Phrases: None

16. Other information

Listed in EINECS and TSCA inventories.0

Intended uses: Paints.

References: -(1)Occupational Exposure Limits, EH/40(HSE)

-(2)Deutsche Forschungs gerneinschaft MAK-& BAT-Values.

-(3)A.C.D.Cowley, Polymers Paint Journal, August 7/21, 1985.