# Hangzhou Jiekai Chemicals Co., Ltd.

NO.227, SHIXIN BEILU RD, HANGZHOU, CHINA. Tel: 86-571-83710202 Web: www.jkpigment.com

### Material Safety Data Sheet

# According to 91/155/EEC and ISO 11014-1

| Page:1/3  |  |  |  |
|---|--|--|--|
| 1. Identification of substance and of the company   |  |  |  |
|   |  |  |  |
| Trade Name: PIGMENT VIOLET 23   |  |  |  |
| Hangzhou Jiekai Chemicals Co., Ltd.   |  |  |  |
| NO.227, SHIXIN BEILU RD, XIAOSHAN DISTRICT, HANGZHOU, CHINA.                                  |  |  |  |
| Tel: 86-571-83710202 Fax: 86-571-82163005   |  |  |  |
| 2. <u>Composition/Data on components</u>  |  |  |  |
| Substance: PIGMENT VIOLET 23  |  |  |  |
| CAS No:6358-30-1 EEC Symbol: None R-Phrases: None   |  |  |  |
| 3. <u>Hazards identification</u>  |  |  |  |
| No hazardous effects known  |  |  |  |
| The product is not a substance subject to mandatory marking in accordance with the EEC        |  |  |  |
| Directive 67/584/EEC Or amendments  |  |  |  |
| 4. <u>First Aid measures</u>  |  |  |  |
|   |  |  |  |
| After inhalation: Supply fresh air.   |  |  |  |
| After eye contact: Flush with plenty of pressure water for 15 minutes, occasionally raising   |  |  |  |
| eye lids.   |  |  |  |
| After skin contact: Wash skin with mild soap and water.                                       |  |  |  |
| 5. <u>Fire fighting measures</u>  |  |  |  |
|   |  |  |  |
| Suitable extinguishing media: no restriction  |  |  |  |
| Special hazards caused by the material, its combustion products or resultant gases: none      |  |  |  |
| Special personal protection equipment: none   |  |  |  |
| 6. <u>Accidental release</u>  |  |  |  |
|   |  |  |  |
| <b>Environmental protection conduct:</b> Do not sweep or wash into public stretches of water, |  |  |  |
| sewers or sites of unknown discharge paths.   |  |  |  |
| After spillage/leakage/gas/ leakage: Clean up immediately with wetting or absorbent           |  |  |  |
| material avoiding dusting.  |  |  |  |
| 7. <u>Handling and storage</u><br>Handling:   |  |  |  |
| Usual precautions for nuisance dust should be observed.                                       |  |  |  |
|   |  |  |  |
| Protection against fire and explosion:<br>The product is non-flammable                        |  |  |  |
| Storage:  |  |  |  |
| Store in roofed places at room temperature Keep containers tightly sealed.                    |  |  |  |
| Flammability Class: nor applicable.   |  |  |  |
| rannaomy Class. nor applicable.   |  |  |  |

# Material Safety Data Sheet

# According to 91/155/EEC and ISO 11014-1

| Accord  | C                  |                                    | Page:2/3           |  |
|---|--------------------|------------------------------------|--------------------|--|
| Trade name: PIGMENT VIOLE                                   | ET 23              |                                    |                    |  |
| 8. <u>Exposure controls/pers</u>                            | onal protection    | <u>l</u>                           |                    |  |
| Additional notes for design                                 | of plants equipn   | nent:                              |                    |  |
| No farther details, see sec7                                |                    |                                    |                    |  |
| Components with workplace                                   | ce-related limits  | to be monitored:                   |                    |  |
| Designation   | %                  | Type of data                       | Unit               |  |
| Nuisance dust 10  | 0                  | MAK                                | 6 mg/m3            |  |
|   |                    | TLV/TWA(USA)                       | 10 mg/m3           |  |
| Personal protection equipn                                  | nent:              |                                    |                    |  |
| <b>Respiratory protection:</b>                              |                    |                                    |                    |  |
| An appropriate dust fixer has                               | to be used if a br | eathable dust liberated.           |                    |  |
| 9. Physical and chemical p                                  | <u>properties</u>  |                                    |                    |  |
| Appearance: Violet powder                                   |                    | Odor: mild                         |                    |  |
| Melting point: > 400  |                    | Relative density:1.5               |                    |  |
| Decomposition: None   |                    | Flammability: see 7 handling       |                    |  |
| Molecular formula: C34H22                                   | C12N4O2            | Molecular Weight: 589.47           |                    |  |
| Tinting strength: 95-105% of                                | the standard       | Volatile matter at 105°C: 2.5% max |                    |  |
| Soluble matter in water: 1.5%                               |                    | Oil absorption: $\leq 38$          |                    |  |
| Fastness to light:7-8                                       |                    | Fastness to heat(°C):200           |                    |  |
| Bleeding resistance water: 5                                |                    | Bleeding resistance linseed oil: 4 |                    |  |
| Bleeding resistance acid: 2-3                               |                    | Bleeding resistance alkalis:5      |                    |  |
| Bleeding resistance alcohol:                                | 3                  | Bleeding resistance xyl            | one:5              |  |
| Bleeding resistance ethyl ace                               | etate: 3           |                                    |                    |  |
| 10. <u>Stability and reactivity</u>                         | 7                  |                                    |                    |  |
| Hazardous decomposition p                                   | oroducts           |                                    |                    |  |
| No decomposition at proper                                  | storage and appl   | ication conditions                 |                    |  |
| 11. <u>Toxicological Informat</u>                           | tion               |                                    |                    |  |
| Because of experience with                                  | product mention    | ed there are no recognizable       | e hazards for huma |  |
| beings, if it is correctly used                             | -                  | ed, there are no recognizably      | e nazaras for numa |  |
| 12. <u>Ecological informatio</u>                            | a una uppnea.      |                                    |                    |  |
|   |                    |                                    |                    |  |
| Avoid filtration into waster                                | draining or soil.  |                                    |                    |  |
| 13. Disposal consideration                                  | <u>IS</u>          |                                    |                    |  |
| Uses should acquaint thems                                  | elves with local r | egulations.                        |                    |  |
| Disposal is usually carried of waste material processor; st |                    |                                    | -                  |  |

### **Material Safety Data Sheet**

According to 91/155/EEC and ISO 11014-1

Page:3/3

### Trade name: PIGMENT VIOLET 23

### 14. <u>Transport information</u>

No declaration for transport required

#### 15. <u>Regulatory information</u>

Classified according to the Directives 67/548/EEC, and their varions amendments, and labeled as below:

Warning symbols: None

Warning words: None

Risk Phrases: None

Safety Phrases: None

### 16. Other information

Listed in EINECS and TSCA inventories.0

Intended uses: Paints.

References: -(1)Occupational Exposure Limits, EH/40(HSE)

-(2)Deutsche Forschungs gerneinschaft MAK-& BAT-Values.

-(3)A.C.D.Cowley, Polymers Paint Journal, August 7/21, 1985.