Hangzhou Jiekai Chemicals Co., Ltd.

TECHNICAL DATE SHEET

Fast Yellow HGR

Product Description

Color Index Pigment Yellow 191

C.I. No. 18795

CAS No. 129423-54-7 EC No. 403-530-4 Chemical Family Mono azo

Technical Properties

Fast Yellow HGR is a brilliant yellow pigment, with good light fastness, weather fastness, durability, easily dispersed and good migration resistance. good heat Resistance, usually use for plastic

Application

Recommended for PVC, EVA, Fibre, RUB, PP, PE and powder coating.

Suggested for PU, PC, PS, PA and water-decorative paint.

Physical Date

e Density (g/cm3)	1.6
Moisture (%)	≤1.5
Water Soluble Matter (%)	≤1.0
Oil Absorption (ml/100g)	35-45
Electric Conductivity (us/cm)	≤500
Fineness (80mesh)	≤5.0
PH Value	7.0-8.0

Thick Color Light Color

Fastness Properties(5=Execllent, 1=Poor)

Acid Resistance	5
Alkali Resistance	5
Alcohol Resistance	5
Ester Resistance	5
Benzene Resistance	5
Ketone Resistance	5
Soap Resistance	5
Bleeding Resistance	5
Migration Resistance	5
Heat Resistance (°C)	280
Light Fastness (8=Excellent)	7

Note: The color shade you see in this web is different with the color shade of our products because of effect of monitor, so the color shade is only for your reference.